

TECHNICAL SPECIFICATION




NAME: LED Wall Pack

P/N: PRD-WP-60WB1

Advantage:

- UL cUL DLC certificate
- IP65 Internal driver, Input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.



TECHNICAL SPECIFICATION

Application:

- ◆ entrance lighting, courtyard lighting
- ◆ Industrial lighting, Outdoor landscape lighting;
- ◆ Building, The hotel;
- ◆ Wall lighting area and so on.

Product Specifications

Product name	LED Wall Pack
Part No	PRD-WP-60WB1
Dimension	360.5*235*194 mm 14.19x9.25x7.64 in

Technical Characteristic

Color temperature	3000K	3500K	4000K	4500K	5000K	5700K
CRI	>80					
Lumen	6600-7200LM					
Lumen Efficacy	110-120LM/W					
Input Power	60W					
Viewing Angle	110 Degree					
Input Voltage	100-277VAC 50/60Hz					
Driver model	China Brand Driver					
PF	>0.9					
Waterproof Rating	IP65					

Materials

LED Type	2835, 0.5W
LED QTY	210 PCS
Housing	Aluminum(ADC12) +PC
Housing color	Brown



TECHNICAL SPECIFICATION

Operating Temperature	-20°C TO 45°C
Operating Humidity	20%-90% RH
Storage Temperature	-30°C TO 80°C
Storage Humidity	10%-95%
Application	Outdoor / Indoor
Safety Certification	UL、cUL、DLC
Warranty Time	5 Years

Others

Light Distribution Testing Parameters

DATA OF LAMP		PHOTOMETRIC DATA Eff: 116.21 lm/W			
MODEL		I _{max} (cd)	2694	S/MH (C0/180)	1.22
NOMINAL POWER (W)	60	LOR (%)	100.0	S/MH (C90/270)	0.47
RATED VOLTAGE (V)	120	TOTAL FLUX (lm)	7051.5	η UP, DN (C0-180)	19.4, 69.7
NOMINAL FLUX (lm)	7051.5	CIE CLASS	SEMI-D.	η UP, DN (C180-360)	0.5, 10.4
LAMPS INSIDE	1	η up (%)	19.9	CIBSE SHR NOM	1.00
TEST VOLTAGE (V)	120.0	η down (%)	80.1	CIBSE SHR MAX	1.15



TECHNICAL SPECIFICATION

Package

Lamps Net Weight: 3.7kg /pc or 8.16lbs /pc

	Size	Qty/ Carton	Weight/ Carton
Cardboard	400*300*245 mm 15.75x11.81x9.64 in	1	4.8 KG 10.58 LBS



Notice For User

- ◆ Please turn off power before install or change assembly parts.
- ◆ The input voltage and lamps should be matched, after connecting the power line, Please make sure the wiring section is insulated.
- ◆ No-professionals, must not install and disassemble the lamps.

TECHNICAL SPECIFICATION

Trouble Shootings

Troubles	Check points
Flickering of the light	Turn off the power and turn on again in 3 minutes. If same phenomena occur, then call agencies
Out of working	Please check the connection